



Technical Datasheet

Parking bay stopTriangle



Manufacturer

Richard Brink GmbH & Co KG
Metal goods manufacture and distribution
Görlitzer Str. 1
33758 Schloß Holte-Stukenbrock
Phone: 0049 (0)5207 9504-0
Fax: 0049 (0)5207 9504-20



Product description

The Triangle car park stop is a product for the demarcation and individual marking of parking spaces. Car parks can be reserved in a very special way by individual marking with laser lettering. The car park stop acts as a frontal boundary in front of buildings and as drive-over protection in front of green areas, footpaths, etc. The car park stop prevents damage to vehicles at the front and rear caused by bumping into building walls.

Dimensions

Width:	90 mm
Hight:	90 mm
Delivery length:	700 mm / 1.800 mm

Materials used

We only use European material from Germany, Sweden, France and Italy for our products.

Material specification planting wall

Stainless steel (V2A)

Material thickness: 3.0 mm

Processing and care instructions

Dust particles of other metals or general cutting of components with flying sparks on the product should generally be avoided. If dust particles or soiling of other metals are present, these must be removed immediately using appropriate cleaning agents.

The car park stops must not be cleaned with strong acids or alkalis, but by hand with a broom or, if necessary, with a high-pressure cleaner.

Further installation and utilisation instructions as well as information on the material can be found at:

<https://www.richard-brink.de/en/downloads/overview.html>