



## Technical data sheet

# Cast iron grates Hydra Linearis 7 x 7 mm



### Manufacturer

Richard Brink GmbH & Co KG  
Metal goods manufacture and distribution  
Görlitzer Str. 1  
33758 Schloß Holte-Stukenbrock  
Phone: 0049 (0)5207 9504-0  
Fax: 0049 (0)5207 9504-20



## Product description

The Hydra Linearis 7 x 7 mm heavy-duty longitudinal bar grating is a box gutter cover grating.

The grate is made of stainless steel V2A.

## Load class

The Hydra Linearis 7 x 7 mm longitudinal grating is designed for load class D400 (*trafficable*).

## Dimensions

Inlet width	Nominal dimension	Height	Bar thickness
150 mm	DN 100	20 mm	7 x 7 mm
200 mm	DN 150	20 mm	7 x 7 mm

The standard grating length is 1,000 mm in each case.

Special sizes are possible on customer request.

## Inlet cross-sections of the grates

Inlet width 150 mm: 642 cm<sup>2</sup>/m

Inlet width 200 mm: 920 cm<sup>2</sup>/m

## Slip resistance

The slip resistance of the grates corresponds to slip rating class R10.

## Clear mesh size

The requirements of the German Social Accident Insurance (*DGVU-Information 208-007 Gratings - Selection and Operation*) are met. The clear mesh width must not exceed 10 mm to ensure safe walking and driving on.



## **Accessories**

- Corners, factory prepared, side length 500 mm

## **Materials used**

We use only European material from Germany, Sweden, France and Italy for our grates.

## **Material specification**

Stainless steel V2A (1.4301)

## **Rust lock**

Grate locks are integrated in the product as standard.

## **Processing and care instructions**

The grates can be cut to size. However, it must be ensured that the cutting medium (e.g. *saw blade, cutting disc, etc.*) is absolutely clean or does not contain any components of other metals, as otherwise corrosion may occur.

Dust particles of other metals or general cutting of components with flying sparks on the product are generally to be avoided. If dust particles or soiling of other metals are present, these must be removed immediately with appropriate cleaning agents.

The grates must not be cleaned with strong acids or bases, but by hand with a broom or, if necessary, with a high-pressure cleaner.

Further installation & usage instructions as well as information on the material can be found at:

<https://www.richard-brink.de/en/downloads/overview.html>